



FEATURES

- 8 zones expandable to 32
- EN Grade 2, Class II
- 1 A PSU (500mA auxiliary)
- 500 event log
- 31 User codes
- On-board digi-modem
- 8 Set groups
- ABS and metal case versions

The QX32i Control Panel is ideally suited for domestic and light commercial installations that are required to meet EN50131-1 Grade 2, environmental class II. The panel is housed in either an ABS or metal case, which has ample room for a 7Ah back up battery and a 4 circuit expander if required.

Featuring 8 diagnostic circuit inputs, 6 TX outputs and a built in digi-modem, the QX is equipped with all you need for a communicated system with advanced features and functions. The addition of a video server and Guardstation (GSR) software allows for verification of events. The ability to programme 8 set-groups and 8 areas gives total flexibility usually only found in larger systems.

As with all Guardall panels, the QX32i uses a common set of bus-based peripherals including the new Mini Keypad designed to reduce the risk of false activations using proximity tokens instead of PIN codes.



Integration Starts Here!

| SPECIFICATIONS | QX32i |
|------------------------|---|
| EN 50131-1 & PD6662 | Grade 2, Class II |
| Max. circuits | 8 on-board expands to 32 |
| PSU | 0.5A (aux) 0.5A (battery) |
| XiB busses | 1 fuse protected |
| Max. security users | 31 + engineer |
| Max. access users | N/A |
| Areas | 8 |
| Set groups | 8 |
| Sub systems | 4 |
| Max keypads | 8 |
| Output modules | 2 |
| TX outputs | 6 |
| Ethernet modules | 1 |
| Access modules | N/A |
| Talkback modules | 4 |
| Wireless modules | External, 2 max |
| Max. transmitters | 16 |
| Max. keyfobs | 8 |
| Video servers/cameras | 2 server, 32 cameras |
| XiB (bus) detectors | 16 |
| Custom responses | 5 |
| Telephone numbers | 8 |
| Alarm formats | Contact ID, SIA Level 3, Ademco Fast, Superfast, Speech S.M.S. and Guardall |
| Digi-modem | On-board |
| Diagnostics | All circuits, PSU, Battery & Peripherals |
| Security log size | 500 |
| Access log size | N/A |
| Supported GSRs | 4 |
| Remote control/service | Through GSR software |
| Serial connection | On-board |
| Schedules | 2 |
| Holidays | 14 |
| Battery capacity | 1 x 7Ahr in the case |
| Case material | ABS 5VA or 1.2mm mild steel |
| Case dimensions (mm) | 300 x 220 x 85 or 300 x 315 x 76 |
| Unit packed weight | 2kgs or 4kgs |

ORDER INFORMATION

| | |
|---------------|-------------------------------------|
| W76476 | QX32i Panel (ABS case) |
| W76522 | QX32i Panel + LCD Prox |
| W76523 | QX32i Panel + LCD Prox + Visonic RX |
| W76481 | QX32i Panel (metal case) |

Guardall is a worldwide supplier.
For contact information, please go to www.guardall.com