



## FEATURES

- 8 zones expandable to 16
- EN Grade 2, Class II
- 1 A PSU (500mA auxiliary)
- 250 event log
- 15 User codes
- On-board digi-modem
- 4 part sets
- Silent and Quick Set Options

The RX16i Control Panel is ideally suited for domestic and light commercial installations that are required to meet EN50131-1 Grade 2, environmental class II. The panel is housed in an ABS case, which has ample room for a 7Ah battery for back up and a 4 circuit expander if required.

Featuring 8 diagnostic circuit inputs, 6 TX outputs and a built-in digi-modem, the RX is equipped with all you need for a communicated system with advanced features and functions. The integration of Visonic™ wireless allows a hybrid system to be installed and gives greater flexibility during the system design and installation process. The addition of a video server and Guardstation (GSR) software allows for verification of events.

As with all Guardall panels, the RX16i uses a common set of bus-based peripherals including the new Mini Keypad designed to reduce the risk of false activations using proximity tokens instead of PIN codes.



**Integration Starts Here!**

SPECIFICATIONS	RX16i
<b>EN 50131-1 &amp; PD6662</b>	Grade 2, Class II
<b>Max. circuits</b>	8 on-board expands to 16
<b>PSU</b>	0.5A (aux) 0.5A (battery)
<b>XiB busses</b>	1 fuse protected
<b>Max. security users</b>	15 + engineer
<b>Max. access users</b>	N/A
<b>Areas</b>	4
<b>Set groups</b>	N/A
<b>Sub systems</b>	N/A
<b>Max keypads</b>	4
<b>Output modules</b>	1
<b>TX outputs</b>	6
<b>Ethernet modules</b>	1
<b>Access modules</b>	N/A
<b>Talkback modules</b>	2
<b>Wireless modules</b>	Internal option or external, 2 max
<b>Max. transmitters</b>	16
<b>Max. keyfobs</b>	4
<b>Video servers/cameras</b>	1 server, 16 cameras
<b>XiB (bus) detectors</b>	8
<b>Custom responses</b>	2
<b>Telephone numbers</b>	8
<b>Alarm formats</b>	Contact ID, SIA Level 3, Ademco Fast, Superfast, Speech S.M.S. and Guardall
<b>Digi-modem</b>	On-board
<b>Diagnostics</b>	All circuits, PSU, Battery & Peripherals
<b>Security log size</b>	250
<b>Access log size</b>	N/A
<b>Supported GSRs</b>	1
<b>Remote control/service</b>	Through GSR software
<b>Serial connection</b>	On-board
<b>Schedules</b>	2
<b>Holidays</b>	N/A
<b>Battery capacity</b>	1 x 7Ahr in the case
<b>Case material</b>	ABS 5VA
<b>Case dimensions (mm)</b>	300 x 220 x 85
<b>Unit packed weight</b>	2kgs (ABS case)

## ORDER INFORMATION

<b>W76469</b>	RX16i Panel (ABS case)
<b>W76518</b>	RX16i Panel + Mini LCD + Fob Pack
<b>W76519</b>	RX16i Panel + Mini LCD + Fob Pack + Visonic RX
<b>W76520</b>	RX16i Panel + LCD Prox
<b>W76521</b>	RX16i Panel + LCD Prox + Visonic RX

**Guardall is a worldwide supplier.**  
For contact information, please go to [www.guardall.com](http://www.guardall.com)